



HAL
open science

Mineralization of synthetic and industrial pharmaceutical effluent containing trimethoprim by combining electro-Fenton and activated sludge treatment

Dorsaf Mansour, Florence Fourcade, Isabelle Soutrel, Didier Hauchard, Nizar Bellakhal, Abdeltif Amrane

► To cite this version:

Dorsaf Mansour, Florence Fourcade, Isabelle Soutrel, Didier Hauchard, Nizar Bellakhal, et al.. Mineralization of synthetic and industrial pharmaceutical effluent containing trimethoprim by combining electro-Fenton and activated sludge treatment. *Journal of the Taiwan Institute of Chemical Engineers*, 2015, 53, pp.58-67. 10.1016/j.jtice.2015.02.022 . hal-01132840

HAL Id: hal-01132840

<https://hal-univ-rennes1.archives-ouvertes.fr/hal-01132840>

Submitted on 19 May 2015

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

1 **Mineralization of synthetic and industrial pharmaceutical effluent**
2 **containing trimethoprim by combining electro-Fenton and activated sludge**
3 **treatment**

4
5 Dorsaf Mansour^{a,b,c,d}, Florence Fourcade^{a,d}, Isabelle Soutrel^{b,d}, Didier Hauchard^{b,d}, Nizar
6 Bellakhal^c, Abdeltif Amrane^{a,d*}

7
8 ^aUniversité de Rennes 1, Ecole Nationale Supérieure de Chimie de Rennes, CNRS, UMR
9 6226, 11 allée de Beaulieu, CS 50837, 35708 Rennes Cedex 7, France

10 ^bEcole Nationale Supérieure de Chimie de Rennes, CNRS, UMR 6226, 11 allée de Beaulieu,
11 CS 50837, 35708 Rennes Cedex 7, France

12 ^cUnité de recherche de Catalyse d'Electrochimie de Nanomatériaux et leurs applications et de
13 didactique CENAD, Institut National des Sciences Appliquées et de Technologie (INSAT),
14 B.P.N°676, 1080 Tunis Cedex, Tunisie

15 ^dUniversité Européenne de Bretagne, 5 boulevard Laënnec, 35000, France

16

17

18

19

20

21

22

23 *Corresponding author: Phone: (+33) 2 23 23 81 55; Fax: (+33) 2 23 23 81 20;

24 abdeltif.amrane@univ-rennes1.fr

25

26

1 **Abstract**

2 A combined process coupling an electro-Fenton and a biological degradation was investigated
3 in order to mineralize synthetic and industrial pharmaceutical effluent containing
4 trimethoprim, a bacteriostatic antibiotic. Electro-Fenton degradation of trimethoprim was
5 optimized by means of a Doehlert experimental design, showing that 0.69 mM Fe²⁺, 466 mA
6 and 30 min electrolysis time were optimal, leading to total trimethoprim removal, while
7 mineralization remained limited, 12% for 30 min electrolysis times. The aromatic and
8 aliphatic by-products were identified and a plausible degradation pathway was proposed.
9 Biodegradability was improved, since the BOD₅/COD ratio increased from 0.11 initially to
10 0.32 and 0.52 after 30 and 60 min electrolysis times respectively, confirmed by activated
11 sludge culture, 47 and 59% mineralization of the byproducts from electrolysis.

12 The relevance of the proposed combined process was then confirmed on an industrial
13 pharmaceutical effluent. Its electrolysis under the above conditions showed an almost total
14 removal of trimethoprim after 180 min of electrolysis, while TOC removal remained low, 14
15 and 16% for 180 and 300 min reaction times, respectively. Overall removal yields of the
16 industrial effluent during the combined process were therefore 80 and 89% for 180 and 300
17 minutes of effluent pretreatment followed by 15 days activated sludge culture, respectively.

18

19 **Keywords:** Trimethoprim; Combined processes; Electro-Fenton; Activated sludge culture;
20 Pharmaceutical effluents; Mineralization.

21


22 **1. Introduction**

23 In these last years, antibiotics were considered to be an emerging environmental problem due
24 to their continuous entry and persistence in the aquatic ecosystem [1]. This pollution proceeds
25 from human excretion after drug administration and passes through wastewater treatment

1 plants (WWTPs). Comparatively, veterinary antibiotics do not undergo WWTPs treatment
 2 and may directly enter surface water. Animal manure, dispersed in the fields as fertilizer, can
 3 contaminate soil and consequently surface and groundwater [2]. Moreover, waste effluents
 4 from manufacture can also be considered as significant points of contamination [3].

5 Most conventional treatments applied in WWTPs were unsuccessful in the removal of
 6 antibiotics [4–6]. Consequently, the accumulation and persistence of these compounds in the
 7 environment can threat aquatic and terrestrial ecosystems [1]. Moreover, antibiotics residues
 8 in water are also suspected to be responsible for the production of resistant microorganisms,
 9 causing serious problems of public health, namely difficulties in treating pathologies and
 10 imbalance of microbial ecosystems [7]. Therefore, efficient and economical methods must be
 11 developed as an urgent need to remove these pollutants.

12 Advanced oxidation processes (AOPs) are potentially powerful methods; they are based on
 13 the generation of hydroxyl radicals ($\cdot\text{OH}$) which are very reactive and non-selective oxidizing
 14 agents, leading to the degradation of organic pollutants by hydrogen atom abstraction reaction
 15 (Eq. (1)), electron transfer (Eq. (2)), or electrophilic addition to π systems (Eq. (3)) [8–12].
 16 These processes involve chemical, photochemical or electro-chemical techniques such as
 17 Fenton, UV/ or H_2O_2 /ozonation, photo-Fenton, heterogeneous photocatalysis and electro-
 18 Fenton [11–15].





22 Nevertheless, AOP used for complete mineralization can be expensive, and hence its
 23 combination with a biological treatment can significantly reduce operating costs [16]. This
 24 combination is especially suitable when microorganisms present in activated sludge are not
 25 able to metabolize the parent compound; the AOP, applied as a pre-treatment step, may

1 enhance the overall biodegradability by transforming this parent compound into easily
2 biodegradable and less toxic intermediates, preventing cellular lysis [1,17,18].

3 The present work intends to perform three objectives. The first one is the use of Doehlert
4 methodology design to optimize the electro-Fenton operating conditions for the removal of
5 trimethoprim (TMP) i.e. its degradation into organic by-products; the second aim is to
6 combine electro-Fenton process and biological treatment for the mineralization of TMP i.e. its
7 transformation into water, carbon dioxide and inorganic ions; and the last one is the validation
8 of the combined process through the remediation of an industrial pharmaceutical effluent.

9 Electro-Fenton is an electrochemical advanced oxidation process based on the continuous
10 generation of H₂O₂ in an acidic medium through the electrochemical reduction of O₂ at the
11 cathode (Eq. (4)). The generated H₂O₂ reacts with the added Fe²⁺ ions to produce hydroxyl
12 radicals ([•]OH) and Fe³⁺ ions via the Fenton's reaction (Eq. (5)), which is favored by the
13 catalytic action of the Fe³⁺/Fe²⁺ system, mainly from the regeneration of Fe²⁺ by the cathodic
14 reduction of Fe³⁺ (Eq. (6)) [8,11,13,19]. At the anode, oxygen is formed by the oxidation of
15 water (Eq. (7)). Moreover, the method and the involved reactor are easy to handle and to use.



20 As mentioned above, the chosen target compound is trimethoprim (C₁₄H₁₈N₄O₃,
21 290.32 g mol⁻¹, CAS 738-70-5), a bacteriostatic antibiotic commonly prescribed in
22 combination with sulfamethoxazole for the treatment of infectious diseases in humans. It is
23 also widely used in veterinary medicine, for prevention and treatment of infections and as a
24 growth promoter. The removal of TMP in wastewater treatment plants has been reported to be
25 less than 10% [20]. Therefore, the TMP (water solubility of 400 mg L⁻¹ at 25°C) has been

1 detected in many environmental monitoring studies in the concentration range of $\mu\text{g L}^{-1}$
2 (0.1 to 5 $\mu\text{g L}^{-1}$) in WWTP effluents [21].

3

4 **2. Materials and Methods**

5 *2.1. Chemicals*

6 Trimethoprim (98%) was purchased from Sigma Aldrich (Saint Quentin Fallavier, France).
7 $\text{FeSO}_4 \cdot 7\text{H}_2\text{O}$ (purity 99%) and Na_2SO_4 (purity 99%), used as a catalyst source and inert
8 supporting electrolyte respectively, were provided from Acros Organics (Thermo Fisher
9 Scientific, Illkirch, France). Acetonitrile (purity 99.9%) (HPLC grade) was also obtained from
10 Sigma Aldrich. The initial pH of the solutions was adjusted using analytical grade sulfuric
11 acid from Acros. All solutions were prepared in ultra-pure water and all the other chemicals
12 used for analysis were purchased from Acros Organics and Sigma Aldrich.

13

14 *2.2. Characterization of the pharmaceutical effluent*

15 The effluent used in this study was supplied by a pharmaceutical industry located in north
16 Tunisia, collected in a container, closed and stored in obscurity at 4°C. This effluent
17 contained a high TMP concentration of 3.56 g L^{-1} and was characterized by a conductivity of
18 4.36 mS cm^{-1} , a COD of 438.50 g L^{-1} and a TOC of 125.40 g L^{-1} . Before treatment, the
19 effluent was diluted to obtain an initial TMP concentration of 0.2 mM, in order to conduct the
20 treatment in the same conditions as the synthetic solution.

21

22 *2.3. Analytical determinations*

23 *2.3.1. High Performance Liquid Chromatography (HPLC)*

24 The evolution of trimethoprim concentrations was monitored by HPLC using a Waters 996
25 system equipped with Waters 996 PDA (Photodiode Array Detector) and Waters 600LCD

1 Pump. The separation was achieved on a Waters C₁₈, (5 μm; 4.6 × 250 mm) reversed-phase
2 column. The eluent consisted of a mixture of acetonitrile/ultra-pure water (20/80 v/v) buffered
3 at pH 3 with phosphoric acid and 0.01 M Na₂HPO₄, delivered at a flow rate of 1 mL min⁻¹.
4 Detection of trimethoprim was carried out at 204 nm.

5

6 2.3.2. Chemical Oxygen Demand (COD) measurements

7 Chemical Oxygen Demand (COD) was measured by means of Nanocolor[®] tests CSB 160 and
8 1500 from Macherey-Nagel (Düren, Germany). The amount of oxygen required for the
9 oxidation of the organic and mineral matter at 148°C for 2 h was quantified after oxidation
10 with K₂Cr₂O₇ at acidic pH [22].

11

12 2.3.3. Total Organic Carbon (TOC) measurements

13 The solutions were filtered on Sartorius Stedim Minisart 0.40 μm GF prefilters (Goettingen,
14 Germany). TOC was measured by means of a TOC-V_{CPH/CPN} Total Organic Analyzer
15 Shimadzu. Organic carbon compounds were combusted and converted to CO₂, which was
16 detected and measured by a non-dispersive infrared detector (NDIR). Reproducible TOC
17 values were always obtained using the standard NPOC (Non Purgeable Organic Carbon)
18 method. For each sample, each measurement was triplicated [16].

19

20 2.3.4. Activated Sludge Preparation

21 Activated Sludge used in this study was collected from a local wastewater treatment plant
22 (Rennes Beaurade, Bretagne, France). It was washed several times by successions of
23 centrifugation, supernatant withdrawing and resuspension of pellet in water, in order to
24 remove any residual carbon or mineral nutrients.

25

1 2.3.5. Biological Oxygen Demand (BOD₅) measurements

2 BOD₅ measurements were carried out in Oxitop IS6 (WTW, Alès, France). The following
3 mineral basis was used for all experiments (g L⁻¹): MgSO₄·7H₂O, 22.50; CaCl₂, 27.50; FeCl₃,
4 0.15; NH₄Cl, 2.00; Na₂HPO₄, 6.80; KH₂PO₄, 2.80. Washed activated sludge was added in
5 order to have 0.05 g L⁻¹ initial concentration of dry matter. The BOD₅ value was initially
6 estimated based on the COD value experimentally measured, BOD₅ = COD/1.46. The range
7 of expected BOD₅ measurement was then deduced and hence led to the volumes of sample, of
8 activated sludge solution and nitrification inhibitor (10 mg L⁻¹ solution of N-allylthiourea)
9 which have to be added to the shake flask of the Oxitop apparatus. Similar protocol was
10 applied for the control sample except that it was replaced by a solution of easily
11 biodegradable compounds, namely glutamic acid (150 mg L⁻¹) and glucose (150 mg L⁻¹).
12 Before use, KOH was added to achieve neutral pH (7.0 ± 0.2). Similar protocol was also
13 considered for the blank solution, for which the sample was replaced by water to have a
14 negligible BOD₅ value.

15

16 2.3.6. Ultra-pressure liquid chromatography-tandem mass spectrometry (UPLC-MS/MS)

17 Aromatic by-products of trimethoprim were separated using a Waters (Acquity UPLC) liquid
18 chromatographic system (Milford, USA). 5 µL of samples were injected into an Acquity BEH
19 C₁₈ column (2.1 mm × 100 mm, 1.7 µm) thermostated at 45°C. Isocratic elution was
20 performed with a mixture of acetonitrile/ultra-pure water (30/70 v/v) (with the addition of
21 0.1% formic acid when needed), delivered at a flow rate of 400 µL min⁻¹. A Quattro Premier
22 triple-quadrupole mass spectrometer (Manchester, UK) equipped with an electrospray
23 ionization source (ESI) was used for by-products detection. MS/MS detection was performed
24 in negative or positive mode with a capillary voltage of ±3 KV. The desolvation gas flow
25 (N₂) was set to 750 L h⁻¹. The source temperature and desolvation gas temperature were

1 120°C and 350°C, respectively. The analytical device was controlled by Micromass Masslynx
2 4.1 software.

3

4 2.3.7. Ion chromatography (IC)

5 Generated carboxylic acids were identified by ion chromatography (Dionex DX120), coupled
6 to a conductivity detector, using an anion-exchange column Dionex AS19 (4 × 250 mm)
7 equipped with a Dionex AG19 guard column (4 × 50 mm) coupled to a ASRS suppressor.
8 The eluent gradient was generated using the Dionex ECG-KOH Elu GenII cartridge; it was as
9 follows: 0-10 min: 10 mM isocratic; 10-25 min: gradient from 10 to 45 mM; 25-35 min:
10 45 mM isocratic with a flow rate of 1 mL min⁻¹.

11

12 2.4. Experimental Procedure

13 2.4.1. Electro-Fenton process

14 The degradation of the organic matter by the electro-Fenton process was carried out in a 1 L
15 undivided cylindrical glass cell equipped with two electrodes. The dimensions of the carbon
16 felt piece placed on the inner wall of the cell (Le Carbone Lorraine RVG 4000 – Mersen,
17 Paris La Défense, France), which was used as the cathode, were 260 mm × 80 mm. Its
18 specific area, measured by the BET method was 0.7 m² g⁻¹, its thickness was 12 mm, its
19 density was 0.088 g cm⁻³ and its carbon yield was 99.9%. The anode was a cylindrical
20 platinum electrode (50 mm × 20 mm) located in the center of the electrochemical reactor to
21 have a good potential distribution. Prior to electrolysis, compressed air was bubbled for 10
22 min through the solution at a flow rate of 450 cm³ min⁻¹ to saturate the aqueous solution with
23 oxygen.

24 The pH of the solutions was adjusted to 3 by sulfuric acid (H₂SO₄). A catalytic quantity of
25 FeSO₄·7H₂O was introduced into the cell just before the beginning of the electrolysis. The

1 electrodes were connected to a DC power supply (Metrix, model AX 322, Chauvin Arnoux
2 Group, Paris, France) operating in galvanostatic mode to control the current intensity. The
3 ionic strength was maintained constant by the addition of 0.05 M Na₂SO₄. The electrolytic
4 solution was in circulation with the help of a peristaltic pump (flow rate of 2 L min⁻¹). The
5 temperature was maintained at 18°C and the initial synthetic solution or the industrial
6 pharmaceutical effluent was diluted to achieve an initial trimethoprim concentration of
7 0.2 mM.

8 2.4.2. Biological treatment

9 Culture media were prepared in duplicate in 500 mL serum bottles containing 200 mL of
10 synthetic trimethoprim solution or pharmaceutical effluent, beforehand electrolyzed. Minerals
11 were spiked in the medium as highly concentrated solutions to reach the following initial
12 composition (mg L⁻¹): Na₂HPO₄, 334; K₂HPO₄, 208; KH₂PO₄, 85; CaCl₂, 27.4; MgSO₄.7H₂O,
13 22.6; NH₄Cl, 2; FeCl₃.6H₂O, 0.26; and the initial pH was adjusted to 7. Activated sludge was
14 added in order to have 1 g L⁻¹ initial concentration of dry matter. Cultures were agitated at
15 350 rpm and kept at room temperature (25°C). Samples (5 mL) were taken regularly, filtered
16 through 0.45 µm-syringe filters and injected for TOC measurements.

17

18 2.5. Doehlert experimental design

19 Doehlert experimental design [23] was used to determine the optimal operating conditions for
20 the degradation of trimethoprim. The influence of three factors: current intensity (U₁), initial
21 Fe²⁺ concentration (U₂) and electrolysis time (U₃) were studied. The analyzed response (Y)
22 was the removal rate of trimethoprim. The Doehlert matrix consists of N experiments with
23 $N = K^2 + K + 1$, where K is the number of variables. For K = 3, the matrix comprised 13
24 experiments which were uniformly distributed within the space of the coded variables (X_i).
25 The number of replicates in the central point of the design was fixed at 3 (experiments 13-15)

1 in order to obtain an estimation of the experimental error. The transformation of natural
2 variables (U_i) into coded variables (X_i) was made according to the following equation [24]:

$$3 \quad X_i = \left[\frac{U_i - U_{i(0)}}{\Delta U_i} \right] \alpha_i \quad (8)$$

4 Where $U_{i(0)}$ is the value of U_i at the center of the study domain, ΔU_i is the variation step and
5 α_i is the maximum coded value of X_i : $\alpha_1 = 1$; $\alpha_2 = \sqrt{3} / 2$; $\alpha_3 = \sqrt{6} / 3$.

$$6 \quad U_{i(0)} = \frac{\text{upper limit of } U_i + \text{lower limit of } U_i}{2} \quad (9)$$

$$7 \quad \Delta U_i = \frac{\text{upper limit of } U_i - \text{lower limit of } U_i}{2} \quad (10)$$

8 For the Doehlert experimental design construction, the retained domain for each variable (300
9 $< U_1/\text{mA} < 500$; $0.050 < U_2/\text{mM} < 1.000$ and $6 < U_3/\text{min} < 30$) was determined after
10 preliminary tests (data not shown).

11 The experimental response associated to the Doehlert matrix is represented by a quadratic
12 polynomial model:

$$13 \quad Y = b_0 + b_1 X_1 + b_2 X_2 + b_3 X_3 + b_{11} X_1^2 + b_{22} X_2^2 + b_{33} X_3^2 + b_{12} X_1 X_2 + b_{13} X_1 X_3 + b_{23} X_2 X_3 \quad (11)$$

14 Where Y is the experimental response, b_0 is a constant of the model, b_i is the estimation of the
15 main effects of the factor i , b_{ii} is the estimation of the second order effects and b_{ij} is the
16 estimation of the interactions between factor i and factor j .

17 The calculation of coefficients is carried out through the least squares method by means of

$$18 \quad B = (X^T X)^{-1} X^T Y \quad (12)$$

19 Where B is the vector of estimates of the coefficients, X is the model matrix, X^T is the
20 transposed model matrix and Y is the vector of the measured response.

21 The statistical significance of the model was checked using the variance analysis (ANOVA).

22 The relationship between the response and the experimental variables was graphically
23 illustrated by plotting the three-dimensional response surface and the two dimensional
24 isoresponse curves. NEMRODW Software [25] was used for data calculation and treatment.

1 3. Results and Discussion

2 3.1. Determination of the optimal conditions for the removal of TMP

3 The performances of the electro-Fenton process depend on various operating parameters, like
 4 current intensity, initial ferrous ions concentration and electrolysis time [26]. The optimal
 5 conditions of these variables, for the removal of trimethoprim, have been investigated by the
 6 use of Doehlert matrix. The experimental design is represented in Table 1.

7 The obtained responses (TMP removal (%)) were used to compute the polynomial model
 8 coefficients, leading to propose the following model equation:

$$9 \quad Y = 98.9 + 2.7 X_1 + 1.5 X_2 + 13.2 X_3 - 2.2 X_1^2 - 3.4 X_2^2 - 13.2 X_3^2 + 0.8 X_1X_2 + 0.7 X_1X_3 -$$


$$10 \quad 2.6 X_2X_3 \quad (13)$$

11 The variance analysis for the fitted model indicated that the model was statistically
 12 meaningful (P-value < 0.01) (Table 2). Moreover, the correlation coefficients ($R^2 = 0.98$ and
 13 $R^2_{Adjusted} = 0.95$) were high, implying that in the studied domain more than 95% of the
 14 response variability was explained by the second-order polynomial predicted equation (Eq.
 15 (13)). Consequently, one can conclude that the response Y is adequately described by the
 16 polynomial model, and so the generated equation can be used to predict the Y-values in the
 17 studied domain.

18 Furthermore, the isoresponse curves of TMP removal and the corresponding three-
 19 dimensional representations can be seen in Fig. 1. The graphic analysis of these figures
 20 showed that increasing electrolysis time enhanced the removal of trimethoprim. Indeed, a
 21 higher rate of trimethoprim removal could be reached when the reaction time would vary
 22 from 20 to 30 minutes (Fig. 1a-d).

23 It can also be seen that TMP removal rate was improved when the initial Fe^{2+} concentration
 24 was located between 0.64 and 0.74 mM (Fig. 1c and d), most likely due to a higher production
 25 of hydroxyl radicals in the presence of more Fe^{2+} ions in the electro-Fenton reaction [27].

1 However, the use of high ferrous ions concentration ($[\text{Fe}^{2+}]_0 > 0.74 \text{ mM}$) led to a decrease of
 2 the removal efficiency, probably due to the consumption of $\cdot\text{OH}$ by the excessive ferrous ions
 3 according to equation (14), decreasing the quantity of this radical and hence inhibiting the
 4 degradation reaction [8,27].



6 Moreover, it can be noted that an increase of the applied current intensity would increase the
 7 removal efficiency; the maximum TMP removal rate was obtained when the current intensity
 8 was ranging between 455 and 477 mA (Fig. 1e and f). This trend can be explained by the
 9 excess production of hydrogen peroxide and an increased regeneration rate of Fe^{2+} that would
 10 promote hydroxyl radical production [28]. Besides, at a higher current intensity ($I > 477 \text{ mA}$)
 11 the TMP removal rate decreased; this behavior can be attributed to the $4e^-$ reduction of O_2
 12 leading to the formation of H_2O (Eq. (15)), which inhibits H_2O_2 formation reaction (Eq. (4))
 13 [29]. In addition, at current values higher than 477 mA, the hydrogen gas evolution, at the
 14 cathode (Eq. (16)), compete with the formation of H_2O_2 [30]. This situation reduces the
 15 production of hydroxyl radicals and consequently, decreases the removal efficiency of
 16 trimethoprim.



19

20 *3.2. Electro-Fenton pretreatment of TMP*

21 The removal of trimethoprim was carried out in the optimal operating conditions deduced
 22 from the Doehlert matrix, namely $[\text{Fe}^{2+}]_0 = 0.69 \text{ mM}$ and $I = 466 \text{ mA}$, leading to a rapid and
 23 total TMP removal within 30 min pretreatment (Fig. 2a). Contrarily, mineralization and
 24 oxidation yields remained low, 12 and 21% for 30 and 60 min electrolysis times for the
 25 former (Fig. 2a), and 29 and 56% from an initial amount of $86 \text{ mg L}^{-1} \text{ O}_2$ for the latter after 30
 26 and 60 min pretreatment respectively (Fig. 2b). This suggested the formation of organic

1 intermediate products, as confirmed at the examination of the HPLC profiles (data not
2 shown), showing that the disappearance of TMP was accompanied by the formation of several
3 intermediates products. This behavior is coherent with the fast destruction of TMP and TOC
4 decrease and can be explained by the oxidation of generated products by hydroxyl radicals
5 [31].

6 *3.3. Improvement of the biodegradability*

7 In order to follow the evolution of the biodegradability profile during the electro-Fenton
8 pretreatment, the samples were analyzed for BOD₅ and COD, showing a ratio of 0.11 for the
9 target molecule confirming its recalcitrance and the need for its oxidation prior to a biological
10 treatment (Fig.2b), while the BOD₅/COD ratio increased to 0.32 and 0.52 after 30 and 60 min
11 electrolysis times, namely above the limit of biodegradability (0.4 [32]) after 60 min
12 pretreatment. From this and owing to the total TMP removal after only 30 min electrolysis, in
13 addition to TMP removal part of by-products was also oxidized after 60 min pretreatment.

14

15 *3.4. Identification of intermediate products and pathway of TMP degradation*

16 The electro-Fenton degradation of 0.2 mM trimethoprim aqueous solution containing
17 0.69 mM ferrous ions and 50 mM Na₂SO₄ at pH 3 and 466 mA constant current led to the
18 formation of aromatic by-products and short-chain carboxylic acids. The identification of the
19 main aromatic by-products was carried out by UPLC-MS/MS; it was based on the analysis of
20 the Total Ion Chromatogram (TIC) and the corresponding mass spectra. The proposed
21 structures were also determined according to the structure of the parent compound and the
22 molecular weight (MW) of the by-products. Among the degradation products, six compounds
23 were confirmed by comparing their retention time and their molecular weight with those of
24 commercially available standard compounds (Table 3); their evolution during electrolysis was

1 presented in Fig. 3. Besides, generated carboxylic acids were identified by ion
2 chromatography and their retention times were compared with standard compounds (Table 3).
3 The obtained results allowed suggesting a degradation pathway for the electro-Fenton
4 oxidation of trimethoprim (Fig. 4). As can be seen, the cleavage of the central methylene
5 group of TMP, at the beginning of electrolysis, was accompanied by the formation of 1,2,3-
6 trimethoxybenzene (MW 168) and 2,4-diamino-5-pyrimidinemethanol (MW 140) which has
7 already been reported during the TiO₂ photocatalysis of TMP [33]. The compound MW 168
8 was further transformed to 3,4,5-trimethoxyphenol (MW 184) through hydroxylation reaction.
9 In addition, the compound MW 140 was converted into 2,4-diaminopyrimidine-5-
10 carbaldehyde (MW 138) which was presumably further oxidized by $\cdot\text{OH}$ to give 2,4-
11 diaminopyrimidine-5-carboxylic acid (MW 154). These latter by-products have been proven
12 by earlier studies [21,33]. Furthermore, the hydroxylation of the 2,4-diaminopyrimidine
13 portion of TMP yielded the phenolic product 6-hydroxytrimethoprim (MW 306) which has
14 also been identified during the $\cdot\text{OH}$ oxidation of TMP [20]. 2,4-diamino-6-hydroxypyrimidine
15 (MW 126) and (3,4,5-trimethoxyphenyl)methanol (MW 198) were formed during the
16 cleavage of the central methylene group of MW 306 by the attack of $\cdot\text{OH}$. The latter
17 compound (MW 198) has already been reported during the electrochemical degradation of
18 TMP at boron-doped diamond electrode [34]. Moreover, we presume that 2,6-
19 diaminopyrimidine-4,5-diol (MW 142) was the result of hydroxylation of the compound MW
20 126. In addition, the product (MW 198) was attacked by $\cdot\text{OH}$ to form the 3,4,5-
21 trimethoxybenzaldehyde (MW 196). The latter degradation product, which has been proven
22 by earlier study [33], can also undergo oxidation leading to 3,4,5-trimethoxybenzoic acid
23 (MW 212).

24 The observation of Fig. 2a and Fig. 3 shows that the disappearance of TMP and the formation
25 of intermediate compounds took place simultaneously. As can be seen, the major aromatic by-

1 products were 2,4-diaminopyrimidine-5-carbaldehyde and 3,4,5-trimethoxybenzaldehyde,
2 their formations were very fast, they reached their maximum concentrations (196.5 and
3 $91 \mu\text{g L}^{-1}$ respectively) at 5 min and completely disappeared within 40 and 50 min,
4 respectively. Whereas, 3,4,5-trimethoxyphenol and 2,4-diamino-6-hydroxypyrimidine
5 reached their maximal accumulation values (lower than $2 \mu\text{g L}^{-1}$) after 10 min of treatment
6 and then their concentrations decreased until complete disappearance. It was found that the
7 concentration of 1,2,3-trimethoxybenzene remained at small steady-state values during the
8 electrolysis. On the other hand, the 3,4,5-trimethoxybenzoic acid concentration increased
9 rapidly attaining a maximum concentration of $4 \mu\text{g L}^{-1}$ at 5 min of electrolysis and then
10 followed a slow degradation kinetic. Finally, all aromatic by-products would be further
11 oxidized by $\cdot\text{OH}$ through ring cleavage reactions into short-chain aliphatic carboxylic acids,
12 such as acetic acid (MW 60), glyoxylic acid (MW 74), oxalic acid (MW 90) and succinic acid
13 (MW 118). The time-course evolution of some carboxylic acids was followed; the obtained
14 results showed that glyoxylic and succinic acids appeared during the first minutes of
15 treatment, reaching concentrations of 11.5 and 2 mg L^{-1} after 60 min of electrolysis.
16 According to Haidar *et al.* [35], the action of hydroxyl radicals on the aromatic intermediates
17 is easier than on the carboxylic acids, which have a good resistivity and are hardly oxidizable
18 by $\cdot\text{OH}$.

19

20 3.5. Biological treatment

21 Owing to biodegradability improvement, activated sludge cultures of pretreated solutions of
22 TMP were carried out in duplicates for 20 days (Fig. 5). 37 and 41% mineralization were
23 obtained after 4 and 6 days of culture for the solutions pretreated during 30 and 60 minutes,
24 respectively (Fig. 5). This behavior can be attributed to a readily assimilation of some of the
25 degradation products by microorganisms [36]. Low mineralization rates can be then observed

1 beyond this time until reaching 47 and 59% on the 20th day for the solutions electrolyzed
2 during 30 and 60 minutes, respectively (Fig. 5). From this, the level of mineralization
3 observed during activated sludge culture increased with the pretreatment time. It is
4 noteworthy that in the absence of pretreatment, no noticeable TMP biodegradation was
5 observed (Fig. 5), in agreement with its low BOD₅/COD ratio, 0.11 (Fig. 2b).

6 It should be noted that possible biosorption of TMP or the degradation products from the
7 pretreatment was checked and was found to be not significant (data not shown).

8 Moreira *et al.* [37], have studied the mineralization of 20.0 mg L⁻¹ of TMP by electro-Fenton
9 process, with a 10 cm² BDD anode and a 10 cm² carbon PTFE air diffusion cathode. The
10 treatment was performed using a low Fe²⁺ dose of 2.0 mg L⁻¹, a low current density of 5
11 mA·cm² and a pH of 3.5; it has led to a 14% mineralization after 180 min reaction.

12

13 *3.6. Application to an industrial pharmaceutical effluent*

14 The pretreatment of an industrial pharmaceutical effluent was carried out in the same
15 operating conditions as for the synthetic solution (Fig. 6). As shown in Fig. 6a, continuous
16 TMP removal was observed during the oxidation of the industrial effluent until reaching 98%
17 after 180 minutes. The rate of TMP degradation in the industrial effluent was therefore slower
18 than in the synthetic solution; this behavior may be due to the competitive consumption of
19 hydroxyl radicals by other organic compounds contained in the real effluent, since TMP
20 accounted for only 6% of the organic content of the industrial effluent (Tables 1 and 2). A low
21 level of mineralization was concomitantly observed, 14 and 16% for 180 and 300 minutes
22 electrolysis times (Fig. 6a), as well as a relatively low level of oxidation, 18 and 20% from an
23 initial amount of 8770 mg L⁻¹ O₂ after 180 and 300 minutes of pretreatment respectively (Fig.
24 6b). These results can be explained by the generation of intermediate compounds
25 simultaneously with the degradation of the target compound, as confirmed at the examination

1 of the HPLC profiles (data not shown). The low BOD₅/COD ratio (0.14 – Fig. 6b) of the
2 industrial effluent confirmed the need for a pretreatment prior to a biological treatment; while
3 after electrolysis, the solutions became biodegradable since the BOD₅/COD ratios increased
4 to 0.45 and 0.47 for 180 and 300 minutes pretreatment (Fig. 6b). The corresponding
5 biological treatments were therefore carried out and are displayed in Fig. 7. The
6 mineralization yields observed were close to 70% after about 10 days of culture for the
7 effluent pretreated during 180 minutes and final mineralization yields were 76 and 87% for
8 180 and 300 minutes of effluent pretreatment, respectively (Fig. 7). Contrarily, in the absence
9 of pretreatment, the rate and the yield of mineralization were significantly lower, since only
10 15% TOC removal was observed after 8 days of culture and about 50% at the end of culture
11 (15th day). Overall removal yields of the industrial effluent during the combined process were
12 therefore 80 and 89% after 180 and 300 minutes of effluent pretreatment, respectively.

13 It should also be noted that as for the synthetic solution possible biosorption of the organic
14 content of the industrial effluent or the degradation products from the pretreatment was
15 checked and was found to be negligible (data not shown).

16 The higher levels of mineralization observed for the industrial effluent if compared to the
17 synthetic solution should be underlined. Indeed, TMP contributed for only 6% of the carbon
18 content of the industrial effluent, and hence at least part of this organic content was also
19 oxidized during pretreatment and mineralized during biological treatment. Indeed, in the
20 absence of pretreatment, no TMP degradation was observed (Fig. 5), while significant
21 mineralization was observed at the end of the biological treatment of the industrial effluent
22 (Fig. 7). Furthermore, for 30 and 180 minutes pretreatment of the synthetic solution and the
23 industrial effluent, namely the time needed for a total TMP removal (Figs.2a and 6a),
24 important mineralization was observed for the industrial effluent, 70% after about 10 days

1 biological treatment (Fig. 7), while only 47% after 20 days culture on the synthetic solution
2 (Fig. 5).

3

4 **4. Conclusions**

5 Doehlert experimental design was used to determine the optimal operating conditions for the
6 degradation of trimethoprim by the electro-Fenton process. The obtained results showed a
7 total TMP removal after an electrolysis time of 30 min, for an initial ferrous ions
8 concentration of 0.69 mM and using a current intensity of 466 mA. The degradation of TMP
9 was accompanied by the formation of aromatic by-products and short-chain carboxylic acids.
10 Based on the identified intermediates, a plausible degradation pathway was proposed.

11 Trimethoprim pretreatment was carried out in the optimal operating conditions deduced from
12 the Doehlert matrix, leading to low levels of mineralization, 12 and 21% after 30 and 60 min
13 electrolysis times respectively. Simultaneously, an improvement of the biodegradability was
14 noted, (0.32 and 0.52 from an initial BOD₅/COD ratio of 0.11). Therefore, biological
15 treatments were performed during 20 days and showed that the level of mineralization
16 increased with the electrolysis time, from 47 to 59% for 30 and 60 min pretreatment times.

17 In order to confirm the relevance of the proposed combined process, an industrial
18 pharmaceutical effluent was electrolyzed under the same conditions, showing an almost total
19 TMP removal (98%), while the mineralization yields remained low, 14 and 16% after 180 and
20 300 minutes electrolysis times, respectively. Moreover, the BOD₅/COD ratio increased from
21 0.14 to 0.45 and 0.47 proving the enhancement of biodegradability of the pretreated effluent.

22 The corresponding biological treatments led to 76 and 87% of mineralization after 15 days.
23 Overall removal yields of the industrial effluent during the combined process were therefore
24 80 and 89% for 180 and 300 minutes of effluent pretreatment, respectively. An increase of the

1 pretreatment time entailed therefore a better biodegradability resulting in a higher
2 mineralization of the electrolyzed solution during the subsequent biological culture.

3

4

1 **References**

- 2 [1] Homem V, Santos L. Degradation and removal methods of antibiotics from aqueous
3 matrices – A review. *J Environ Manage* 2011;92:2304–47.
- 4 [2] Sharma VK. Oxidative transformations of environmental pharmaceuticals by Cl₂, ClO₂,
5 O₃, and Fe(VI): Kinetics assessment. *Chemosphere* 2008;73:1379–86.
- 6 [3] Mompelat S, Le Bot B, Thomas O. Occurrence and fate of pharmaceutical products and
7 by-products, from resource to drinking water. *Environ Int* 2009;35:803–14.
- 8 [4] Adams C, Wang Y, Loftin K, Meyer M. Removal of Antibiotics from Surface and
9 Distilled Water in Conventional Water Treatment Processes. *J Environ Eng*
10 2002;128:253–60.
- 11 [5] Gobel A, Mcardell C, Joss A, Siegrist H, Giger W. Fate of sulfonamides, macrolides,
12 and trimethoprim in different wastewater treatment technologies. *Sci Total Environ*
13 2007;372:361–71.
- 14 [6] Vieno NM, Härkki H, Tuhkanen T, Kronberg L. Occurrence of Pharmaceuticals in River
15 Water and Their Elimination in a Pilot-Scale Drinking Water Treatment Plant. *Environ*
16 *Sci Technol* 2007;41:5077–84.
- 17 [7] Bailón-Pérez MI, García-Campaña AM, Cruces-Blanco C, del Olmo Iruela M. Trace
18 determination of β -lactam antibiotics in environmental aqueous samples using off-line
19 and on-line preconcentration in capillary electrophoresis. *J Chromatogr A*
20 2008;1185:273–80.
- 21 [8] Brillas E, Sirés I, Oturan MA. Electro-Fenton Process and Related Electrochemical
22 Technologies Based on Fenton's Reaction Chemistry. *Chem Rev* 2009;109:6570–631.
- 23 [9] Ghoneim MM, El-Desoky HS, Zidan NM. Electro-Fenton oxidation of Sunset Yellow
24 FCF azo-dye in aqueous solutions. *Desalination* 2011;274:22–30.

- 1 [10] Oturan MA. An ecologically effective water treatment technique using electrochemically
2 generated hydroxyl radicals for in situ destruction of organic pollutants: Application to
3 herbicide 2,4-D. *J Appl Electrochem* 2000;30:475–82.
- 4 [11] Oturan MA, Oturan N, Edelahe MC, Podvorica FI, Kacemi KE. Oxidative degradation of
5 herbicide diuron in aqueous medium by Fenton's reaction based advanced oxidation
6 processes. *Chem Eng J* 2011;171:127–35.
- 7 [12] Özcan A, Şahin Y, Oturan MA. Complete removal of the insecticide azinphos-methyl
8 from water by the electro-Fenton method – A kinetic and mechanistic study. *Water Res*
9 2013;47:1470–9.
- 10 [13] Loaiza-Ambuludi S, Panizza M, Oturan N, Özcan A, Oturan MA. Electro-Fenton
11 degradation of anti-inflammatory drug ibuprofen in hydroorganic medium. *J Electroanal*
12 *Chem* 2013;702:31–6.
- 13 [14] Shu H, Chang M. Decolorization effects of six azo dyes by O₃, UV/O and UV/HO
14 processes. *Dyes Pigments* 2005;65:25–31.
- 15 [15] Yang H, An T, Li G, Song W, Cooper WJ, Luo H, et al. Photocatalytic degradation
16 kinetics and mechanism of environmental pharmaceuticals in aqueous suspension of
17 TiO₂: A case of β -blockers. *J Hazard Mater* 2010;179:834–9.
- 18 [16] Oller I, Malato S, Sánchez-Pérez JA. Combination of Advanced Oxidation Processes
19 and biological treatments for wastewater decontamination—A review. *Sci Total Environ*
20 2011;409:4141–66.
- 21 [17] Ballesteros Martín MM, Sánchez Pérez JA, García Sánchez JL, Casas López JL, Malato
22 Rodríguez S. Effect of pesticide concentration on the degradation process by combined
23 solar photo-Fenton and biological treatment. *Water Res* 2009;43:3838–48.

- 1 [18] Mansour D, Fourcade F, Huguet S, Soutrel I, Bellakhal N, Dachraoui M, et al.
2 Improvement of the activated sludge treatment by its combination with electro Fenton
3 for the mineralization of sulfamethazine. *Int Biodeterior Biodegrad* 2014;88:29–36.
- 4 [19] Garcia-Segura S, Garrido JA, Rodríguez RM, Cabot PL, Centellas F, Arias C, et al.
5 Mineralization of flumequine in acidic medium by electro-Fenton and photoelectro-
6 Fenton processes. *Water Res* 2012;46:2067–76.
- 7 [20] Luo X, Zheng Z, Greaves J, Cooper WJ, Song W. Trimethoprim: Kinetic and
8 mechanistic considerations in photochemical environmental fate and AOP treatment.
9 *Water Res* 2012;46:1327–36.
- 10 [21] Michael I, Hapeshi E, Osorio V, Perez S, Petrovic M, Zapata A, et al. Solar
11 photocatalytic treatment of trimethoprim in four environmental matrices at a pilot scale:
12 Transformation products and ecotoxicity evaluation. *Sci Total Environ* 2012;430:167–
13 73.
- 14 [22] Fourcade F, Yahiat S, Elandaloussi K, Brosillon S, Amrane A. Relevance of
15 Photocatalysis prior to Biological Treatment of Organic Pollutants - Selection Criteria.
16 *Chem Eng Technol* 2012;35:238–46.
- 17 [23] Doehlert DH. Uniform Shell Designs. *J R Stat Soc Ser C Appl Stat* 1970;19:231–9.
- 18 [24] Hammami S, Ouejhani A, Bellakhal N, Dachraoui M. Application of Doehlert matrix to
19 determine the optimal conditions of electrochemical treatment of tannery effluents. *J*
20 *Hazard Mater* 2009;163:251–8.
- 21 [25] Mathieu D, Nony J, Phan-Tan-Luu R. New Efficient Methodology for Research using
22 Optimal Design (NEMRODW) Software, LPRAI, Univ. Aix-Marseille III, France 2000.
- 23 [26] Mansour D, Fourcade F, Bellakhal N, Dachraoui M, Hauchard D, Amrane A.
24 Biodegradability Improvement of Sulfamethazine Solutions by Means of an electro-
25 Fenton Process. *Water Air Soil Pollut* 2012;223:2023–34.

- 1 [27] Panizza M, Cerisola G. Electro-Fenton degradation of synthetic dyes. *Water Res*
2 2009;43:339–44.
- 3 [28] Atmaca E. Treatment of landfill leachate by using electro-Fenton method. *J Hazard*
4 *Mater* 2009;163:109–14.
- 5 [29] Özcan A, Şahin Y, Koparal AS, Oturan MA. Degradation of picloram by the electro-
6 Fenton process. *J Hazard Mater* 2008;153:718–27.
- 7 [30] Masomboon N, Ratanatamskul C, Lu M-C. Chemical oxidation of 2,6-dimethylaniline
8 by electrochemically generated Fenton's reagent. *J Hazard Mater* 2010;176:92–8.
- 9 [31] Hammami S, Bellakhal N, Oturan N, Oturan MA, Dachraoui M. Degradation of Acid
10 Orange 7 by electrochemically generated $\bullet\text{OH}$ radicals in acidic aqueous medium using a
11 boron-doped diamond or platinum anode: A mechanistic study. *Chemosphere*
12 2008;73:678–84.
- 13 [32] Salles NA, Fourcade F, Geneste F, Floner D, Amrane A. Relevance of an
14 electrochemical process prior to a biological treatment for the removal of an
15 organophosphorous pesticide, phosmet. *J Hazard Mater* 2010;181:617–23.
- 16 [33] Sirtori C, Agüera A, Gernjak W, Malato S. Effect of water-matrix composition on
17 Trimethoprim solar photodegradation kinetics and pathways. *Water Res* 2010;44:2735–
18 44.
- 19 [34] De Amorim KP, Romualdo LL, Andrade LS. Electrochemical degradation of
20 sulfamethoxazole and trimethoprim at boron-doped diamond electrode: Performance,
21 kinetics and reaction pathway. *Sep Purif Technol* 2013;120:319–27.
- 22 [35] Haidar M, Dirany A, Sirés I, Oturan N, Oturan MA. Electrochemical degradation of the
23 antibiotic sulfachloropyridazine by hydroxyl radicals generated at a BDD anode.
24 *Chemosphere* 2013;91:1304–9.

1 [36] Fontmorin J-M, Fourcade F, Geneste F, Floner D, Huguet S, Amrane A. Combined
2 process for 2,4-Dichlorophenoxyacetic acid treatment—Coupling of an electrochemical
3 system with a biological treatment. *Biochem Eng J* 2013;70:17–22.

4 [37] Moreira FC, Garcia-Segura S, Boaventura RAR, Brillas E, Vilar VJP. Degradation of the
5 antibiotic trimethoprim by electrochemical advanced oxidation processes using a carbon-
6 PTFE air-diffusion cathode and a boron-doped diamond or platinum anode. *Appl Catal*
7 *B Environ* 2014;160-161:492–505.

8

9

1 **Table 1** – Doehlert matrix experiments and experimental results.

Experiment Number	Coded variables			Real variables			Results Y (%)
	X ₁	X ₂	X ₃	Current intensity:	Fe ²⁺ concentration:	Electrolysis time:	
				U ₁ (mA)	U ₂ (mM)	U ₃ (min)	
1	1	0	0	500	0.525	18	100
2	-1	0	0	300	0.525	18	93
3	$\frac{1}{2}$	$\frac{\sqrt{3}}{2}$	0	450	1.000	18	100
4	$-\frac{1}{2}$	$-\frac{\sqrt{3}}{2}$	0	350	0.050	18	92
5	$\frac{1}{2}$	$-\frac{\sqrt{3}}{2}$	0	450	0.050	18	97
6	$-\frac{1}{2}$	$\frac{\sqrt{3}}{2}$	0	350	1.000	18	94
7	$\frac{1}{2}$	$\frac{\sqrt{3}}{6}$	$\frac{\sqrt{6}}{3}$	450	0.683	30	100
8	$-\frac{1}{2}$	$-\frac{\sqrt{3}}{6}$	$-\frac{\sqrt{6}}{3}$	350	0.367	6	78
9	$\frac{1}{2}$	$-\frac{\sqrt{3}}{6}$	$-\frac{\sqrt{6}}{3}$	450	0.367	6	76
10	0	$\frac{\sqrt{3}}{3}$	$-\frac{\sqrt{6}}{3}$	400	0.841	6	80
11	$-\frac{1}{2}$	$\frac{\sqrt{3}}{6}$	$\frac{\sqrt{6}}{3}$	350	0.683	30	100
12	0	$-\frac{\sqrt{3}}{3}$	$\frac{\sqrt{6}}{3}$	400	0.209	30	100
13	0	0	0	400	0.525	18	99
14	0	0	0	400	0.525	18	99
15	0	0	0	400	0.525	18	99

2

3

4 **Table 2** – ANOVA result for TMP removal (%) under electro-Fenton treatment.











Source of variation	Sum of squares	Degrees of freedom	Mean square	F-ratio	P-value
Regression	991.773	9	110.197	28.721	0.00088
Residual	19.184	5	3.8368		
Total	1010.957	14			

5 $R^2 = 0.98$; $R^2_{\text{Adjusted}} = 0.95$.







6

7

1 **Table 3** – Chromatographic identification of the products generated during the electro-Fenton
 2 degradation of trimethoprim.


Compound	Chromatography	Chemical structure	Retention time (min)	ESI mode	Precursor ion (m/z)	Product ions (m/z)
1,2,3-trimethoxybenzene (MW 168)	UPLC-MS/MS		1.98	Positive	169	154 138
2,4-diaminopyrimidine-5-carbaldehyde (MW 138)	UPLC-MS/MS		0.69	Positive	139	97 69
3,4,5-trimethoxyphenol (MW 184)	UPLC-MS/MS		0.91	Negative	183	168 153
2,4-diamino-6-hydroxypyrimidine (MW 126)	UPLC-MS/MS		0.58	Positive	127	85 68 60
3,4,5-trimethoxybenzaldehyde (MW 196)	UPLC-MS/MS		1.63	Positive	197	169 138
3,4,5-trimethoxybenzoic acid (MW 212)	UPLC-MS/MS		0.72	Negative	211	167 152
Acetic acid (MW 60)	IC		4.2			
Glyoxylic acid (MW 74)	IC		4.5			
Oxalic acid (MW 90)	IC		5.4			
Succinic acid (MW 118)	IC		14.6			

1 **Figure captions**




1 **Figure 1.** (a) Contour plots of TMP removal versus the electrolysis time (min) and the current
 2 intensity (mA); (b) corresponding three-dimensional plot; (c) contour plots of TMP removal
 3 versus the electrolysis time (min) and the initial Fe^{2+} concentration (mM); (d) corresponding
 4 three-dimensional plot; (e) contour plots of TMP removal versus the initial Fe^{2+} concentration
 5 (mM) and the current intensity (mA); (f) corresponding three-dimensional plot. Results
 6 obtained from the Doehlert matrix (Table 1).

7
8



9
 10 **Figure 2.** (a) Time evolution of TMP and TOC removals; (b) BOD₅/COD ratio and COD
 11 removal. Experimental conditions: $[\text{TMP}]_0 = 0.2$ mM, $[\text{Fe}^{2+}]_0 = 0.69$ mM, $[\text{Na}_2\text{SO}_4] = 50$
 12 mM, pH = 3, T = 18°C, I = 466 mA, V = 1 L.

1




2


3 **Figure 3.** Time-course of aromatic by-products formed during the electro-Fenton treatment.

4 Experimental conditions: $[\text{TMP}]_0 = 0.2 \text{ mM}$, $[\text{Fe}^{2+}]_0 = 0.69 \text{ mM}$, $[\text{Na}_2\text{SO}_4] = 50 \text{ mM}$, $\text{pH} = 3$,


5 $T = 18^\circ\text{C}$, $I = 466 \text{ mA}$, $V = 1 \text{ L}$.




2 **Figure 4.** Pathway proposed for the degradation of TMP by the electro-Fenton process.



1
 2 **Figure 5.** Mineralization during activated sludge cultures of non-pretreated TMP solution and
 3 solutions electrolyzed during 30 min and 60 min. Electro-Fenton pretreatment conditions:
 4 $[TMP]_0 = 0.2 \text{ mM}$, $[Fe^{2+}]_0 = 0.69 \text{ mM}$, $[Na_2SO_4] = 50 \text{ mM}$, $pH = 3$, $T = 18^\circ\text{C}$, $I = 466 \text{ mA}$,
 5 $V = 1 \text{ L}$.



1
2 **Figure 6.** Pretreatment of the industrial pharmaceutical effluent: (a) Time evolution of TMP
3 and TOC removals; (b) BOD₅/COD ratio and COD removal. Experimental conditions:
4 [TMP]₀ = 0.2 mM, [Fe²⁺]₀ = 0.69 mM, [Na₂SO₄] = 50 mM, pH = 3, T = 18°C, I = 466 mA,
5 V = 1 L.



1
2 **Figure 7.** Mineralization during activated sludge cultures of non-pretreated industrial effluent
3 and effluent electrolyzed during 180 and 300 min. Electro-Fenton pretreatment conditions:
4 $[\text{TMP}]_0 = 0.2 \text{ mM}$, $[\text{Fe}^{2+}]_0 = 0.69 \text{ mM}$, $[\text{Na}_2\text{SO}_4] = 50 \text{ mM}$, $\text{pH} = 3$, $T = 18^\circ\text{C}$, $I = 466 \text{ mA}$,
5 $V = 1 \text{ L}$.