





































































The herein exploited ROIMP/CM strategy towards the large-scale preparation of alternated polyether/polyolefin (Method II) successfully provides monocomponent SMPs with promising thermal, mechanical and especially, adhesives characteristics (strain-at-break on wood up to 4.0 MPa) improved as compared to the benchmarked industrial Bostik adhesive Polyvest E100. Envisioned outcomes of these polyether/polyolefin materials are in particular for CASE applications requiring improved resistance to humidity and hydrolysis (as imparted by the polyolefin segments), and for (semi)structural bonding applications in automotive or transport markets. These preliminary results, obtained without optimization nor formulation of the adhesives (*i.e.* free of any additives, fillers or charges), can likely be further improved to enhance their properties and widen the field of application, in particular as viable alternative to current polyurethane adhesives.<sup>50</sup>

## ASSOCIATED CONTENT

### Supporting Information

The Supporting Information including detailed and complementary experimental section and complementary data on the PCOE/P100 copolymers, is available free of charge on the ACS Publications website at DOI: XXXX.

## AUTHOR INFORMATION

### Corresponding Author

\*E-mail: [jean-francois.carpentier@univ-rennes1.fr](mailto:jean-francois.carpentier@univ-rennes1.fr); [sophie.guillaume@univ-rennes1.fr](mailto:sophie.guillaume@univ-rennes1.fr)

### ORCID

Jean-François Carpentier: 0000-0002-9160-7662, Sophie M. Guillaume: 0000-0003-2917-8657

## NOTES











